

DH-NVR6000/6000D/6000DR

128 Channel Super Network Video Recorder



Features

- Max 128 channel IP cameras input with 1080P realtime live view
- Max 384Mbps incoming bandwidth
- Up to 64ch@1080P, 128ch@720P, 128ch@D1 realtime recording
- Up to 6-screen output: 6 HDMI sync output/1 VGA+5 HDMI sync output (Default: 2 HDMI or 1 HDMI +1 VGA)
- Support 16 hot-swap SATA HDDs to better its scalability and flexibility
- Support RAID 0/1/5/6/10/50/60
- Human-oriented Dahua UI
- Compatible with Dahua SDK and seamless integrated to other platforms
- Support Multi-brand network cameras: Dahua, Arecont Vision, AXIS, Bosch, Brickcom, Canon, CP Plus, Dynacolor, Honeywell, Panasonic, Pelco, Samsung, Sanyo, Sony, Videosec, Vivotek and etc.
- ONVIF Version 2.2 conformance
- Redundant power supply module adopted (DH-NVR6000DR)
- Front LCD display (DH-NVR6000D/DH-NVR6000DR)

DH-NVR6000/6000D/6000DR

Technical Specifications



Model	DH-NVR6000	DH-NVR6000D	DH-NVR6000DR
System			
Main Processor	Intel® Core™ i5 Processors		
Operating System	Embedded LINUX		
Motherboard	Embedded Board (Support 7x24 operation)		
Memory	4GB DDR3 (up to 8GB)		
Case	Hot-dipped galvanized sheet steel (1.2mm thickened), High-precise aluminum alloy slide, Patented pull-out rack design		
Fan	Dual ball screw bearing fan, MTBF>100,000h, support replacement during operation		
Interface	Local GUI & WEB GUI		
Video & Audio			
Input	64ch@1080P/128ch@720P/128ch@D1		
Transmission	64ch@1080P/128ch@720P/128ch@D1		
Recording	64ch@1080P/128ch@720P/128ch@D1		
Preview	8ch@1080P/16ch@720P/32ch@D1(Screen 1~2) +16ch@1080P/16ch@720P/16ch@D1(Screen 3~6) (Optional)		
Playback	5ch@1080P/10ch@720P/20ch@D1(Screen 1)		
Recording Resolution	8Mp, 5Mp, 3Mp, 1080P, 720P, 960H, D1, CIF, QCIF, VGA		
Audio	1ch Mic in, 1/1ch audio in/out		
Recording			
Recording Mode	Manual, Schedule(Regular(Continuous), MD(Video detection: Motion detection, Camera blank, Video loss), Alarm), Stop		
Alarm Recording	Video loss, Camera blank, Motion detection, External alarm		
Backup Mode	Network download/USB HDD/USB CD&DVD-RW/eSATA Device		
Display			
Interface	6 HDMI, 1 VGA (Default: 2 HDMI, 1 VGA)		
Video Output	6 HDMI, or 1ch VGA(or built-in LCD) & 5ch HDMI sync video output (Default: 2 HDMI, or 1 VGA(or built-in LCD) & 1ch HDMI sync video output)		
Multi-screen Display	The 1 st screen: 1/4/6/8/9/16/25/36/64 The 2 nd -6 th screens: 4		
Privacy Masking	Four customized zones for privacy masking for each area		
Storage			
Internal HDD	16 SATA ports, up to 64TB		
HDD Mode	Single, Raid 0, Raid 1, Raid 5, Raid 6, Raid 10, Raid 50, Raid 60 (Support global HDD Hot-standby)		

DH-NVR6000/6000D/6000DR

HDD Installation	Independent HDD rack, support hot swap	
Network		
Interface	4 RJ-45 ports (10/100/1000Mbps)	
Ethernet Port	4 Ethernet ports joint working or 4 independent 1000Mbps Ethernet ports	
MD & Alarm		
Motion Detection	Zones: 396(22×18), Sensitivity: 1~6 (level 6 is highest)	
Alarm Input	16ch, low level effective, green terminal interface	
Relay Output	8ch, Relay contact (1A@24VDC), NO/NC programmable, green terminal interface	
Auxiliary Interface		
Front cover	Support hot swap, 7" inch HD LCD (1920x1080/1280x1024/1024x768) (Model -D&-DR)	
USB	4 USB ports (2 on the front-panel, 2 on the rear panel), USB2.0	
eSATA	1 eSATA port	
RS485	1 port, for PTZ control	
General		
Power Supply	AC 100V~240V, 47~63Hz	AC 100V~240V, 47~63Hz , Redundant
Power Consumption	60W (Without HDD)	
Working Environment	-10°C~55°C	
Working Humidity	10%~80% (non-condensation)	
Dimension (W×D×H)	3U, 485mm×448mm×133.2mm	
Weight	20kg (without HDD)	
Installation	Rack-mounted	

DH-NVR6000/6000D/6000DR

Dimensions



Take DH-NVR6000D as an example

Dahua Technology Co., Ltd.

1187 BinAn Road, Binjiang District, Hangzhou, China

Tel: +86-571-87688883

Fax: +86-571-87688815

Email: overseas@dahuatech.com

www.dahuatech.com

*Design and specifications are subject to change without notice.

© 2013 Dahua Technology Co., Ltd.